

STANDARD CIRCULATORS Series "S"

SUBMITTAL

JOB: _____	REPRESENTATIVE: _____
_____	_____
ENGINEER: _____	ORDER NO: _____ DATE: _____
CONTRACTOR: _____	SUBMITTED BY: _____ DATE: _____
_____	APPROVED BY: _____ DATE: _____

PUMP DESIGN DATA	
Pump Model: _____	Flange Size: _____
No. of Pumps: _____	
Note: _____	
Capacity: USgpm (l/s) _____	Temperature: °F (°C) _____
Head: ft. (m) _____	Liquid: _____
Companion Flanges _____	Included _____

Maximum Working Pressure:	125 Psig 863 (kPa)
Maximum Operating Temperature:	225 °F (107 °C)




OPTIONAL EQUIPMENT	
Performance curve _____	See pg. 2

MATERIALS OF CONSTRUCTION		
PART NAME	BRONZE FITTED	ALL BRONZE
Pump Body	Cast Iron	Bronze
Impeller	Non-Ferrous	Non-Ferrous
Bearings	Sleeve-Oil Lubricated	Sleeve-Oil Lubricated
Shaft	Alloy Steel-Copper Sleeve	Alloy Steel-Copper Sleeve
Seal	ARMSEAL Mechanical	ARMSEAL Mechanical
Stationary Seal Face	ARMSEAL Ceramic	ARMSEAL Ceramic
Coupler	S25-S46:Flexible, 4 - Spring;	
	S55-S69:Flexible Spacer Type	
Motor	Single Phase - 1800 RPM - Resilient Mounted Three Phase - 1800 RPM - Resilient Mounted	

DIMENSIONAL DATA								
MODEL	FLANGE SIZE (N.P.T.)	MOTOR*		DIMENSIONS Inches (mm)				WEIGHT lbs (kg)
		H.P.	PHASE & VOLT	A	B	C	D	
S-25	3/4	1/2	1 Phase 115 V	13-3/4 (349)	6-1/2 (165)	11-1/2 (292)	3/4 (19)	20 (9)
	1						3/4 (19)	
	1-1/4						7/8 (22)	
	1-1/2						7/8 (22)	
S-35	2	1/6		15 (581)	8-1/2 (216)	12-1/2 (318)	7/8 (22)	35 (16)
S-45	2-1/2	1/4		19-1/2 (495)	10 (254)	12-1/2 (318)	1 (25)	51 (23)
	3			15-3/4 (400)	10 (254)	12-1/2 (318)	1 (25)	51 (23)
S-46	3	1/3		19-1/2 (495)	12 (305)	16 (406)	1 (25)	82 (37)
S-55	3	1/2	1 Phase 115/230 V or 3 Phase 208-230/460 or 575 V	20 (508)	12 (305)	16-1/2 (419)	1 (25)	85 (39)
S-57	3	3/4		25 (635)	14-1/4 (362)	20 1/4 (514)	1 (25)	135 (61)
S-69	3	1						

Dimensions shown are for reference only. For exact dimensional data, contact factory.


* All single phase motors are equipped with a built-in thermal overload protection. Three phase motors require external overload protection. Conduit box not supplied on 1/2 hp or greater.





PERFORMANCE CURVES

Performance Guaranteed Only At Operating Point Indicated



S. A. Armstrong Limited
23 Bertrand Avenue
Toronto, Ontario
Canada, M1L 2P3
T: (416) 755-2291
F (Main): (416) 759-9101

Armstrong Pumps Inc.
93 East Avenue
North Tonawanda, New York
U.S.A. 14120-6594
T: (716) 693-8813
F: (716) 693-8970

Armstrong Holden Brooke Pullen
Wenlock Way
Manchester
United Kingdom, M12 5JL
T: +44 (0) 161 223 2223
F: +44 (0) 161 220 9660

